

SOS PANEL OUTLET



Specifications

| Parameter Category | Technical Specifications | |
|---------------------|--|--|
| Product name | SOS Panel | |
| Model | Beste™/BestePlus™ | |
| Part No. | GCS-BE-D8-5004-SOSP | |
| Product Description | <ol style="list-style-type: none">1. Product Type2. Outlet Type3. Current Rating4. Mounting5. Fixing | SOS Panel SOS 10/13A (High Voltage), 12VDC(Low Voltage) Flush mounted (Horizontal or Vertical) Screw + clip-in |

Other Details

| | |
|---|--|
| <ol style="list-style-type: none">1. Measurement2. Weight3. Color4. Socket core material5. Faceplate material | 86mm x 86mm 0.2kg Black* Fire retardant polycarbonate Plastic, aluminum or brass metal |
|---|--|

Standard

| |
|----|
| CE |
|----|

Applications

| |
|--|
| Stylish design with perfect craftsmanship, refinement and reliable performance. Recommended for residential or commercial environment. |
|--|

Environment

| | |
|---|--------------------------------------|
| <ol style="list-style-type: none">1. Ambient operation temperature2. Relative humidity3. Application area | -5 to 40 deg C 0 to 95% Indoor |
|---|--------------------------------------|

Cleaning Recommendation

| |
|---|
| It is not recommended to spray cleaning products directly on to electrical switches. Before cleaning, ensure that switches are switched off. Only wipe down with damp or dry cloth. |
|---|

Note: * Other panel color to be decided by customer