

Door Bell/DND/MUR Display Datasheet



Specifications

Parameter Category	Technical Specifications	
Product name	Door Bell/DND/MUR Display	
Compatible Model	Beste™, Stivoll™ or Modisch™	
Part No.	GCS-BE-D8-5003-BDMU	
Product Description	<ol style="list-style-type: none"> 1. Product Type 2. Current Rating 3. Protocol Supported 4. Mounting 5. Fixing 	Doorbell DND display 12VDC (Low Voltage) Low Voltage (485, Dry Contact) Flush mounted (Horizontal or Vertical) Screw + clip-in

Other Details

<ol style="list-style-type: none"> 1. Measurement 2. Color 3. Text 4. Outlet Core material 5. Faceplate material 6. Customization 	86mm x 86mm Black* Customized text with backlit Fire retardant polycarbonate Plastic, aluminum or brass metal The DND/MUR display can be customized for other function**
---	---

Standard

CE.

Applications

Stylish design with perfect craftsmanship, refinement and reliable performance. Recommended for hospitality or commercial environment.
--

Environment

<ol style="list-style-type: none"> 1. Ambient operation temperature 2. Relative humidity 3. Application area 	-5 to 40 deg C 0 to 95% Indoor
---	--------------------------------------

Cleaning Recommendation

It is not recommended to spray cleaning products directly on to electrical switches. Before cleaning, ensure that switches are switched off. Only wipe down with damp or dry cloth.

Note: * Other color to be specified by customer

** Complete door numbering and signage display can be tailored made based on customer's design