

DUAL UNIVERSAL FLOOR SOCKET



Specifications

Parameter Category	Technical Specifications	
Product name	Dual Universal Floor Socket	
Model	GCS-BE-D8-5001-2UFL	
Product Description	<ol style="list-style-type: none">1. Product Type2. Socket Type3. Input voltage4. Contact material5. No of gang6. Mounting7. Fixing	Dual Floor Universal Socket Universal Socket 220VAC 50/60 Hz Brass terminals 2 Floor mounted Floor embedded

Other Details

<ol style="list-style-type: none">1. Measurement2. Weight3. Color4. Socket core material5. Casing material6. Side rim	86mm x 86mm 0.7kg Grey* Fire retardant polycarbonate Metal Option
--	--

Standard

CCC,CE

Applications

Stylish design with perfect craftsmanship, refinement and reliable performance. Recommended for residential or commercial environment.
--

Environment

<ol style="list-style-type: none">1. Ambient operation temperature2. Relative humidity3. Application area	-5 to 40 deg C 0 to 95% Indoor
---	--------------------------------------

Cleaning Recommendation

It is not recommended to spray cleaning products directly on to electrical switches. Before cleaning, ensure that switches are switched off. Only wipe down with damp or dry cloth.

Note: * Other color to be specified by customer